

PLC-XT25 | PLC-XT20

Brilliant Ideas for Your Business.

SANYO

- Resolution, Native: XGA (1,024 x 768)
- Brightness 4,500 (PLC-XT25), 3,800 (PLC-XT20) ANSI lumens
- Motorised horizontal and vertical lens shift function
- Professional connections (5 x BNC, DVI-D)
- Symmetrical design
- Quiet: 30 dB (Eco Mode)
- 3 optional lenses with bayonet lock*
- Vertical operation possible (up to 90°)
- Network integration
- 3-year warranty



* (Lens 0.8 : 1 as of 2007)

PLC-XT25 | PLC-XT20

Brilliant Ideas for Your Business.



TECHNICAL DATA	PLC-XT25	PLC-XT20
Category	Business	
Panel	3 x 1.0" TFT p-Si (4 : 3)	
Projection Lamp	300 W UHP (LMP-105)	
Brightness in ANSI lumens	4,500	3,800
Lamp Life	2,000 h (High Mode), 3,000 h (Eco Mode)	
Fan Noise	30 dB (Eco Mode)	
Standard Lens	F = 1.7 – 2.1/f = 33 – 43 mm	
Aspect Ratio	1.62 – 2.11 : 1	
Throw Distance	1.2 – 10.0 m (You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances.)	
Contrast Ratio	1,000 : 1	800 : 1
Resolution in Pixels	1,024 x 768 (XGA)	
Horizontal Resolution	800 TV lines	
Uniformity	90 %	
Bandwidth/Frequency	140 MHz, horizontal 15–100 kHz, vertical 50–100 Hz	
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N	
Connections	Input 1: 1 x DVI-I (digital/HDCP/analogue), 1 x D-Sub15 (RGB) Input 2: 5 x BNC (RGB/Component/Video) Input 3: 1 x RCA (Composite), 1x Mini DIN 4-pin (S-Video) Audio: 2 x 3.5 mm Stereo jacks for Input 1 and 2, 2 x RCA (R/L mono) for Input 3 Monitor Output: 1 x D-Sub15 Audio Output: 3.5 mm Stereo Jack (variable) Control Input Jack 1: Mini DIN 8-pin (RS232) Control Input Jack 2: USB Type B	Input 1: 1 x DVI-D (digital/HDCP), 1 x D-Sub15 (RGB) Input 2: 5 x BNC (RGB/Component/Video) Input 3: 1 x RCA (Composite), 1x Mini DIN 4-pin (S-Video) Audio: 2 x 3.5 mm Stereo jacks for Input 1 and 2, 2 x RCA (R/L mono) for Input 3 Monitor Output: 1 x D-Sub15 Audio Output: 3.5 mm Stereo Jack (variable) Control Input Jack 1: Mini DIN 8-pin (RS232) Control Input Jack 2: USB Type B
Audio Function	1 W Mono	
Keystone Correction	Vertical +/- 40	
Lens Shift/ U/D Ratio	0 to +50 % (vertical) +/-15 % (horizontal)	
HDTV Compatibility	720p/1,035i/1,080i (HDTV-compatible)	
Computer Compatibility	UXGA/WXGA/SXGA/XGA/SVGA/VGA/Mac	
Zoom/Focus	1.3 x motorised	
Power Consumption	430 W	
Warranty	3 years	
Dimensions (W x H x D)	348 x 156.5 x 444 mm	
Weight	8.7 kg	
Standard Accessories	Operating manual, power cable, IR remote control with laser pointer and mouse function, batteries, USB cable (Type A and B), VGA cable	
Optional Accessories	PJ Net Organizer Plus II (POA-PN03)	
Optional Lenses	Telephoto lens (LNS-T10, throw ratio: 2.12 – 3.46 : 1), Wide-angle lens (LNS-W10, throw ratio: 1.24 – 1.61 : 1)	



Technical specifications subject to change without notice. Date 09/2006

