

PJ506D

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH KEYSTONE CORRECTION

Digitally clear images and video.

ViewSonic's PJ506D DLP® projector is designed to meet the needs of today's mobile presenters. DLP technology delivers crystal-clear images and brilliant color. With 2,000 lumens and an ultra-high 2000:1 contrast ratio (typ) this portable projector is ideal for multimedia lessons in the classroom or dynamic presentations in the boardroom. The PJ506D is a versatile performer with multiple inputs, advanced image processing and support for 720p and 1080i HD signals. The native 800x600 SVGA resolution, digital keystone correction and zoom lens ensure that you'll get the best possible image in virtually any setting. Image reversing functions offer further installation flexibility. The PJ506D is a light-weight, versatile projector that is packed with performance at an affordable price.



VALUE AND PERFORMANCE

- > **Bright in virtually any setting with 2,000 lumens**
Packs 2,000 lumens in just 5.9 lbs. It's the bright choice for mobile presenters.
- > **DLP® technology**
Stunning all digital clarity delivers lifelike color, sharp graphics, and outstanding video.
- > **Ultimate video source flexibility**
Connect a computer or add a video source for dynamic meetings and presentations.
- > **Advanced video features**
Motion adaptive deinterlacer for superior video performance.
- > **Whisper-mode extends lamp life**
Extend the life of your lamp up to 3,000 hours** and reduce noise output.
- > **OnView® controls for superior screen adjustability**
Screen geometry and color adjustments are precisely made via an easy-to-use, on-screen menu.
- > **The best warranty in the business**
Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year limited lamp warranty.***



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic® 

the choice of professionals

PJ506D

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION



Optional Accessories

- Replacement lampRLC-018
- Hard case with wheelsPRJ-HCA-001
- Extended Express Exchange®PRJ-EE-05-03
- Soft case with wheels and laptop bagCASE-006
- Universal ceiling mount kitWMK-005
- VGA to component video adapter . . .ADPT-002
- Wireless G Presentation Gateway . . .WPG-100

PROJECTOR	Type	0.55" DMD, DLP®
	Pixel Format	800x600 SVGA
	Lens	Manual zoom, manual focus
	Zoom Factor	1.1
	Keystone	Vertical ± 15°
DISPLAY	Size	30"-300" (diagonally)
	Throw Distance	39"-390"
	Throw Ratio	1.64-1.96:1
	Lamp	200W, 2,000 hours**
	Brightness	2,000 ANSI lumens
	Contrast Ratio	2000:1
	Aspect Ratio	4:3 (native), 16:9
AUDIO	Speakers	1x1 watts
INPUT SIGNAL	Computer and Video	NTSC M, NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 720p, 1080i)
	Frequency	F _H : 31-79kHz; F _V : 56-85Hz
COMPATIBILITY	PC	Analog: from VGA up to SXGA (scaled)
	Mac®†	Analog: up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	15-pin HD, D-sub cable (x1)
	Composite Video (input)	RCA jack (x1)
	S-Video (input)	Mini-Din 4-pin (x1)
	Component Video (input)	VGA DB-15 to HDTV/component cable*
	Audio (input)	Stereo mini-jack (x1)
	Control	9-pin D-sub for RS232
POWER	Voltage	100-240 VAC, 50/60Hz (universal)
	Consumption	250W (typ)
CONTROLS	Basic	Standby/On, input, menu
	OnView®	Display mode, brightness, contrast, keystone, aspect ratio, blank screen, gamma, white peaking, color temperature, user color, video (sharpness, saturation, tint), display (phase, tracking, H. position, V. position), advance (auto source select, rear, ceiling, eco mode, lamp hours, lamp reset, auto shutdown, OSD timeout, menu position, factory reset), audio (audio, mute)
OPERATING CONDITIONS	Temperature	32-104°F (0-40°C)
	Humidity	10-90% (non-condensing)
	Altitude	0 to +10,000ft sea level
NOISE LEVEL	Normal	36 dB (typ)
	Whisper mode	32 dB (typ)
DIMENSIONS (W x H x D)	Physical (mm)	256mm x 102mm x 223mm
	Physical (in.)	10.1" x 3.4" x 8.8"
WEIGHT	Net	5.9 lb. (2.7 kg)
	Gross	12.5 lb. (5.7 kg)
REGULATIONS		UL, FCC-B, CCC, CE, NOM, PSB, CUL, ICES-003, Argentina TUV/GS, RoHS, IRAM, CB
OTHER		Vertical digital keystone correction, 3:2 pull down, whisper mode
PACKAGE CONTENTS		Projector, power cords, VGA cable, RCA video cable, S-video cable, audio mini-cable, remote control, soft case, lens cap, ViewSonic Wizard CD, Quick Start Guide
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp:***

ViewSonic® 

the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***See ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. The DLP logo is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [13204-00B-10/06] PJ506D-1

For more product information, visit us on the web at ViewSonic.com