

HITACHI
Inspire the Next

CPX5

A HIGHLY COMPACT AND AFFORDABLE 3LCD PROJECTOR, DELIVERING THE PERFECT BALANCE OF FEATURES, PERFORMANCE AND DESIGN

The CPX5 is the ultimate portable projector for the mobile business consumer. Combining stunning features with powerful performance in a lightweight and compact design, the CPX5 delivers whichever way you look at it.


- 2500 (Normal Mode)/
2000 (Whisper Mode) ANSI Lumens
- XGA Resolution
- High Connectivity
- Lightweight and Portable
- PC-less presentation via USB
- Short throw lens - 60"@1.5 m
- Auto Vertical Keystone Correction
- Quick-start (3 seconds)
- Instant OFF
- MyScreen Memory Image Store
- Whiteboard/Blackboard/Greenboard Modes




- **2500 ANSI Lumens (Normal Mode)** – with optical zoom, delivering crisp sharp images, which can be seen perfectly in all lighting conditions.
- **High Connectivity** – 2 x RGB in with audio in/out and versatile video connections.




- **Diagonal Display Size** – The CPX5 provides the biggest possible picture in the tightest space, projecting a 60" screen at 1.5m.




- **Quick Start and Instant Off** – These features are ideal for quick presentations. The image will appear in just 3 seconds after power on and the unit can be instantly powered off after a presentation.
- **Auto Vertical Keystone** – Keystone distortion occurs when the projector is inclined. This is automatically detected by a gravity sensor inside the projector and corrected.



- **Whiteboard/Blackboard/Greenboard Modes** – Images displayed on whiteboards may be too bright, whiteboard mode changes the gamma curve to reduce the peak white brightness allowing users to enjoy the benefits of a bright projector but reducing potential health and safety risks of looking directly into one. Blackboard/Greenboard modes provide better colour balance when projecting onto a coloured background.



- **Security Functions** – CPX5 has an impressive suite of anti-theft measures:



- Pin-lock is a means of in-activating the projector until a user preset key sequence is input
- 'MyScreen lock' allows users to personalise the start up screen with a warning or ownership message and lock this screen with a pin code number
- Transition detector that operates whenever the projection angle or settings are changed from the installed position – this is locked by a numeric pin code.

CPX5 SPECIFICATION

OPTICAL	
LCD Panel	0.63" P-Si TFT x 3
Resolution	XGA
Brightness	Normal Mode 2500 ANSI Lumens Whisper Mode 2000 ANSI Lumens
Contrast Ratio	500:1
Lens	Manual x 1.2 zoom
Lamp	UHB190W
Focus Distance	0.8-7.8m (WIDE), 0.9-9.3m (TELE)
Distance to Width Ratio (:1)	1.3 (WIDE), 1.5 (TELE)
Diagonal Display Size	30"-300" (1.5m@60")

COMPATIBILITY	
Computer Compatibility	IBM Compatible VGA, SVGA, XGA, SXGA/SXGA+, UXGA Capability, MAC 16" (Pixelworks chip)
Video Compatibility	NTSC/PAL/SECAM/PAL-M,N/NTSC4.43 SDTV: 525i(480i), 525p(480p), 625i(576i) HDTV: 750p (720p@60Hz), 1125i(1080i@50/60Hz)
Plug & Play	DCC2B
Frequency Range	FV 56-120Hz, FH 31.5-106KHz

FEATURES	
Keystone Correction	6:1 upward shift, fixed
Digital Keystone	Auto V keystone
Speakers	1 x 1W
Other:	Variable Colour (R, G, B individual), MENU : 17 Language (English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Korean, Traditional Chinese, Swedish, Russian, Finnish, Polish, Turkish), Freeze Function, Magnifying, Digital gamma correction, My Memory, Auto configuration (H-Phase, H-Size, Position), PIN Lock system, Transition detector, MyScreen, Easy Operation : Quick On ,Direct Off, Quick ON, Blackboard mode, Whiteboard mode, Input source naming

CONNECTORS	
Computer Input	2 x 15-pin Mini D-sub
Video Input	1 x Composite 1 x S-Video Jack 1 x Component (shared with D-sub 1)
Audio Input	1 x Stereo Mini Jack
Audio Output	1 x Stereo Mini Jack
Control & Mouse	USB type B x 1 for mouse control
USB type A x 1	• for PC-less presentation

POWER	
Power Supply	100-120V/220-240V
Power Consumption	310W


PHYSICAL	
Dimensions (W x H x D)	274 x 59 x 205mm (excluding feet and extrusions)
Weight	1.7Kg
Noise Level	39dB Normal Mode/33dB Whisper Mode

CERTIFICATION	
UL 60950-1/ cUL, FCC Part15 subpart B class B, CE approval, EN61000-3-2, EN61000-3-3, EN55022, EN55024, EN60950-1, Low voltage directive, WEEE, Other AS/NZS CISPR22 class B	

MISCELLANEOUS	
Lamp indicator light, Power light, Ceiling Mount image, Rear Projection Image	

ACCESSORIES SUPPLIED	
RGB Cable, Remote Control, Batteries, Power Cord, Safety Instruction, Quick Guide, 14 Languages User Manual (English, French, German, Spanish, Italian, Norwegian, Dutch, Portuguese, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish), Soft Sase	

OPTIONAL ACCESSORIES	
Replacement Lamp	DT00821



Screen Size (Diagonal)	Projection Distance (a)		Screen Height (cm)	
	min. (m)	max. (m)	b (top)	c (bottom)
30" (0.8)	0.8	0.9	39.0	7.0
60" (1.5)	1.5	1.9	78.0	13.0
100" (2.5)	2.6	3.1	131.0	22.0
150" (3.8)	3.9	4.7	196.0	33.0
200" (5.1)	5.2	6.2	261.0	44.0
300" (7.6)	7.8	9.3	392.0	65.0

Screen Size (Diagonal)	Projection Distance (a)		Screen Height (cm)	
	min. (m)	max. (m)	b (top)	c (bottom)
30" (0.8)	0.8	1.0	37.0	1.0
60" (1.5)	1.7	2.0	73.0	2.0
100" (2.5)	2.8	3.4	122.0	3.0
150" (3.8)	4.2	5.1	183.0	4.0
200" (5.1)	5.6	6.8	243.0	5.0
300" (7.6)	8.5	10.2	365.0	8.0