

# HP ep9012 Instant Cinema Digital Projector



The HP ep9012 redefines your digital big screen experience as it offers the unique and portable combination of an impressive 2.1 Dolby Digital sound system with integrated subwoofer and a DVD player in one unit without sacrificing on image quality.

**Designed for movie enthusiasts as well as private and commercial presenters, who are looking for the most convenient and easiest way to set-up and enjoy their own big screen theatre without the hassle of connecting to different devices.**

**Plug & play – all you need is a power outlet, the latest blockbuster and a white wall.**

- Integrated high-quality bi-directional 2.1 speakers with powerful 30-watt subwoofer.
- Integrated DVD player, which enables a complete digital signal pass through for best possible image quality.
- Easily navigate through the user friendly menu with the back-lit remote control, by using the same button interface as on the projector.

**Image quality to impress. Get a huge image with amazing clarity, sharpness and colour fidelity.**

- Crystal clear and sharp SVGA resolution (800 x 600 pixels) with 16:9 widescreen and optional 4:3 display capability.
- Outstanding 1600:1 contrast for eye-catching and detail rich images.
- Video optimised 6 segment colour wheel producing extremely natural and realistic colours.
- Latest DLP™ technology preventing the colour degradation experienced over time with LCD projectors.
- High-quality video processing for a flicker-free image and a reduction of potential image noise and interpolations.

**Home cinema on the go.**

- Where there's a wall, there's a way – project your image wherever people want to watch, in the family room, kid's room, at special events and more.
- Use the optional HP Roller Case in order to conveniently bring your complete home cinema wherever you go.

## Technical specifications

|  |  |
|--|--|
| <b>Image contrast</b>                              | 1600:1 (JBMA full-on/full-off)   |
| <b>Display resolution</b>                          | True SVGA (800 x 600) with 16:9 widescreen and optional 4:3 display capability   |
| <b>Resolution supported through scaling</b>        | Scales up from VGA (640 x 480) and scales down from XGA (1024 x 768)   |
| <b>Image technology</b>                            | DLP with 0.55" 12 degree tilt DMD with video optimised 6 segment (RGBRGB) colour wheel   |
| <b>Brightness</b>                                  | 840 ANSI (max) lumens  |
| <b>Noise level</b>                                 | < 34 dB(A), at 23° C   |
| <b>Dimensions (w x d x h)</b>                      | Out of package: 524 x 400 x 320 mm, packaged: 641.4 x 558.8 x 278.6 mm   |
| <b>Weight</b>                                      | Out of package: 10 kg, packaged: 15.3 kg   |
| <b>Colour</b>                                      | 24-bit, 16.7 million colours   |
| <b>Uniformity</b>                                  | 80%  |
| <b>Projector colour coordinates of white point</b> | 0.283, 0.304   |
| <b>Lens</b>  | F/2.4 max, 1.16:1 manual zoom focus  |
| <b>Projection size</b>                             | Adjustable from 0.8 to 6.9 m (diagonal)  |
| <b>Throw distance</b>                              | Approximately 1 to 10 m  |
| <b>Display scan frequency</b>                      | Horizontal frequency: 31-60 kHz, vertical frequency: 43-85 Hz  |
| <b>Offset</b>                                      | 128% of image above the centre line  |
| <b>Keystoneing</b>                                 | Vertical ± 20° (40° total)<br>Advanced electronic keystone correction  |
| <b>Signal interface</b>                            | Via DVI-to-VGA adapter: XGA, SVGA, VGA, Mac, SXGA, Mac LC (13 in), Mac II (13 in), Mac (16 in), Mac (19 in), Mac G4, i Mac DV  |
| <b>User interface</b>                              | Wireless remote for basic functionality with DVD control<br>Lamp broken: red; temperature warning: red; power: blue<br>User-friendly multilingual On Screen Display (OSD)<br>lens cover control  |
| <b>Certifications</b>                              | EU (EMC Directive), USA (FCC Rules), Australia (ACA), New Zealand (MoC), Canada (DoC), China (Requirements for Class B Products, Class A when connected to LANs), Japan (VCC registered), Korea (RRL certified), Taiwan (BCIQ certified)                             |
| <b>Adjustable features</b>                         | Brightness, Contrast, Sharpness, Color saturation, Tint, Color space, Color settings, Keystone, Widescreen mode, Picture mode, Standby lamp delay, DVD player, volume  |
| <b>Speakers/microphone</b>                         | Internal 2.1 speaker system + subwoofer, 60-watt total peak power, 15-watt per channel peak stereo speakers (two speakers' per channel facing front and rear), 30-watt peak subwoofer<br>Stereo sound via headphone-out  |
| <b>Video compatibility</b>                         | NTSC 3.58 MHz and 4.43 MHz; PAL B, D, G, H, I, M, N; SECAM B, D, G, K, K1, L; HDTV (480i/p, 575i/p, 720p, 1080i); DVI with HDCP; PC video up to SXGA (by DVH to VGA adapter)   |
| <b>Internal DVD player compatibility</b>           | DVD-video (including Dolby Digital and Dolby Pro Logic, with DTS passed to digital audio-out), DVD+R/RW, DVD-R/RW, VCD, SVCD, JPG images, MP3 audio, CDDA (standard audio CD), CD-R, CD-R/RW, Kodak Picture CD   |
| <b>External I/O ports</b>                          | Composite video (RCA)<br>S-video (mini-DIN)<br>Component video (3 RCA)<br>DVI<br>5.1 digital audio-out (1 RCA, coaxial)<br>Stereo audio-out (2 RCA)<br>Stereo audio-in (2 RCA)<br>Stereo Headphone jack (mutes built-in speakers)<br>Service port (for service only) |
| <b>Power requirements</b>                          | Universal AC 90-265 V, 47/63 Hz with PFC that meets EN 61000-3-2 Class D for input harmonics   |
| <b>Power consumption</b>                           | 100 to 240 V at 50 to 60 Hz  |
| <b>Lamp</b>  | 210-watt lamp; 4,000 hours lamp life.  |
| <b>Operating environment</b>                       | Environmental ranges: operating temperature: 10 to 40° C, operating humidity: 20 to 80% RH, recommended operating humidity: 20 to 80% RH; storage temperature: 20 to 60° C, storage humidity: 20 to 80% RH   |
| <b>Warranty</b>                                    | One-year limited hardware warranty on digital projector; one-year limited hardware warranty on lamp module or 1,000 lamp hours (which ever comes first).   |
| <b>Service &amp; support</b>                       | 24/7 free email/web support and free telephone support for basic set-up, installation, and troubleshooting in EMEA during and out of warranty; calls will be charged at standard phone rates.  |

## Ordering information

|               |  |
|---------------|--|
| <b>L1752B</b> | HP ep9012 Instant Cinema Digital Projector, AC 3 conductor power cord (3 m, 10 ft), wireless remote control, multi-language user's guide (CD-ROM), multi-language quick start card, battery x 2, warranty card, DVI to VGA adapter |
|---------------|--|

### Cables

|               |                         |
|---------------|-------------------------|
| <b>L1714A</b> | HP HDTV (RGB) 6 m Cable |
| <b>L1715A</b> | HP S-Video 6 m Cable    |

### Digital Imaging Accessories

|               |  |
|---------------|--|
| <b>L1717A</b> | HP SCART to Composite/S-Video with Audio Adapter |
| <b>L1718A</b> | HP DVI to VGA Adapter                            |
| <b>L1731A</b> | HP ep7100 series/ep9012 Lamp Module              |
| <b>L1732A</b> | HP ep9012 Roller Case                            |
| <b>L1740A</b> | HP HDTV Mobile 60-inch Screen                    |
| <b>L1741A</b> | HP HDTV Mobile 80-inch Screen                    |

### Optional warranty extension

|               |                         |
|---------------|-------------------------|
| <b>U4802E</b> | 3 years Unit Exchange   |
| <b>U8136E</b> | 3 years Repair & Return |
| <b>U8228A</b> | 2 years Unit Exchange   |

This projector with region coding 2 is designated for sale in Europe, Middle East and South Africa.

<http://www.hp.com>

For more information, please call your local HP sales office or representative: **Austria:** 0800 242 242, **Algeria:** (0)61 56 45 43, **Bahrain:** 800 728, **Belgium:** (078) 15 20 30 (0.0496 EUR/min), **Bulgaria:** (+359) 2960 1940, **Croatia:** (+385 1) 60 60 200, **Czech Republic:** (00 420 2) 261 108 108 (Prague), **Denmark:** 48 12 10 00, **Egypt:** 532 5222, **Estonia:** (+372) 6813 823, **Finland:** (+358) 0205350 or 0205 350, **France:** (1) 69 82 6060, **Germany:** 0180 532 6222 (12 Cent/min), **Greece:** (01) 678 96 00, **Hungary:** (+36) 1 382-1111, **Iceland:** (354) 570 1000, **Ireland:** + 353 1 6158200, **Israel:** (972) 9 8304848, **Italy:** (02) 92121, **Kazakhstan:** +7 (3272) 980 824, **Latvia:** (371) 800 80 12, **Lithuania:** 8 800 10000 or 8 5 2103333, **Luxembourg:** (+352) 263 160 34, **Middle East:** 00971 4 883 4427, **Morocco (African Region):** +212 22 40 47 47, **Netherlands:** (020) 5476666, **Norway:** 22 735600, **Poland:** infolinia: 0-800 122 622, **Portugal:** (808) 206 001, **Romania:** (+401) 205 3300, **Russia:** +7 (095) 797 35 00, **Saudi Arabia:** 800 124 4646, **Serbia/Montenegro:** +381 11 201 99 00, **Slovakia:** +421-250222111, **Slovenia:** +3861 2307 420, **South Africa:** 0800 118 883, **Spain:** (91) 634 88 00, **Sweden:** (08) 444 2000, **Switzerland:** 0848 88 44 66, **Tunisia:** 71 891 222, **Turkey:** +90 (216) 579 71 71, **UAE:** 8004910, **UK:** 08705 474747, **Ukraine:** +380 44 490 61 20.

DLP™ technology by Texas Instruments offers crystal clear images with superior quality



©2004 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 08/04 5982-7854EEE