



Designer Styling – Big Screen Impact



Small and stylish, the EP720 will deliver life-like presentations and movies up to 300". Great colours, really impressive brightness and easy to use both in the office and at home; with computers, games consoles and DVD players.

- 2200 lumens to highlight the finest detail in ambient light conditions
- Designer styling and compact at 2kg; as versatile on the move as it is when installed
- Optoma Colour Enhancement Technology and 2000:1 contrast gives exceptional colour to create crystal clear presentations and video
- Optoma 10 Year Colour Guarantee*
- Comprehensive PC, Video, DVD and games consoles connectivity includes: VGA, Component & SCART capabilities
- Native SVGA and zoom lens for sharp, detailed images and movies
- DLP® Filter-free design for zero maintenance No routine servicing

Easy to use:

- Fully featured remote control with mouse control
- 5 preset picture modes to adjust the settings to match a variety of different applications
- 15 second start-up and cool down time to reduce both time and money in energy use
- Quick keystone correction

EP720 - Digital DLP® Projector

Single 0.55" SVGA type X DMD chip DLP® Technology by Texas Instruments

16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech &

Full Function Remote Mouse and Direct Source selecting

15 Pin D-Sub VGA (SCART & Component via adaptor)

PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i

1.95 ~ 2.15:1 (Projection Distance:Image Width)

0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3

100-240V, 50-60Hz with PFC Power Supply

One Kensington Lock Port, Password Protection

6 months or 1000 hours - whichever is soonest

EP720 Projection Distance 1.2 - 12m (16:10 Aspect Ratio)

Min. Screer

Height (m)

0.42

0.69

0.87

1.04

1.39

1.74

2.08

2.43

2.78

3.13

3.47

3.82

4.17

260W Maximum < 10W Standby mode

F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus

Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max)

ies x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card

Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batter-

Warranty may vary by country. Please see www.optomaeurope.com or ask your

Max. Diagonal

Image Size (m)

0.94

1 57

1.97

2.36

3.14

3.93

4.72

5.50

6.29

7.08

7.86


8.65

9.43

- Express start-up & cool down
- Built in speaker for multi media use
- Long Lamp Life 3000 hours standard

Optoma Colour Enhancement Technology maximises colour accuracy for deeper saturated colours

Optoma guarantees colour quality will remain as new for 10 years*



Optoma Colour Enhancement Technology



EP720 Remote Control

- 1 Remote Mouse
- 2 Vertical Keystone Correction
- 3 Volume Control
- 4 Brightness Adjustment 5 Contrast Adjustment
- 6 AV Mute
- **Direct Input Source Selection** 7

EP720 Connections

- VGA In Component & SCART via adaptor 8
 - Composite
- 10 S-Video

9

- 11 Audio In
- 12 USB (Remote Mouse)



Optoma recommends Panoview screens Panoview

www.panoview.eu

Optoma Europe Ltd. 42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ

Max. Diagonal

Image Size (Inch)

37.14

61.90

77.38

92.85

123.81

154.76

185.71

216.66

247.61

278.56

309.51

340.47

371.42

Max. Image

Offset (m)

0.23

0.29

0.35 0.47

0.58

0.70

0.82

0.93

1.05

1.17

1.28 1.40

www.optoma.eu

* Optoma guarantee that in normal use, Optoma DLP® colour quality will be indistinguishable from when new. Please note that worn lamps will give slight variance. Exclusion: *(1) Guarantee is voided if the projector is subject to damage through mis-use. (2) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is particularly excessive (3) Guarantee will not apply if lamp brightness is below 50% due to wear or if the projector is not working due to other fault. **Typical lamp life achieved through testing. Will vary according to operational use and environment conditions. Copyright © 2006, Optoma Europe Ltd. All other product names and company names used herein are for identifications purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP® and the DLP logo are registered trademarks of Texas Instruments.

Specifications

Compressed Resolution

Weight / Dimensions (W x D x H)

Native Resolution

Brightness

Noise Level

Remote Control

Lamp Life **Display Technology**

INPUTS:

Audio

Aspect Ratio

Keystone Correction

On Screen Display

Video Compatibility

Displayable Colours

Projection Distance

Horizontal Scan Rate

Vertical Scan Rate

Power Consumption

Operating Conditions

Standard Accessories

Power Supply

Security

RoHS

Warranty

Lamp Warranty

Colour Guarantee

Projection

Distance (m

1.20

2.00

2.50

3.00

4.00

5.00

6.00

7.00

8.00

9.00

10.00

11.00

12.00

For auide purposes only

Max. Horizontal

Image size (m

0.80

1.33

1.67

2.00

2.67

3.33

4.00

4.67

5.33

6.00

6.67

7.33

8.00

and offset information will differ to that of above

Projection Lens

Throw Ratio

Image Size

Uniformity

Contrast

EP720

2000:1

30dB

SVGA 800 x 600

SXGA (1280 x 1024)

2000/1500L (BRIGHT/STD mode)

3000/2000 (STD/BRIGHT mode)**

2 kg / 259 x 188 x 71.5mm

S-Video 4 Pin Mini Din **Composite RCA**

3.5mm Stereo Jack

USB (remote mouse)

± 18 Degrees Vertical

4:3 Native, 16:9 Compatible

1 x 1W Speaker

Arabic

85%

16.7 Million

1.2 - 12m

15 - 100kHz

43 - 85Hz

Compliant

10 Years

Min. Horizontal

Image size (m)

0.67

1.11

1.39

1.67

2.78

3.33

3.89

4.44

5.00

5.56

6.11

6.67

local supplier for details

Max. Screen

Height (m)

0.50

0.83

1.04

1.25

1.67

2.08

2.50

2.92

3.33

3.75

4.17

4.58

5.00

EP720 is capable of 16:9 & 4:3 aspect ratio projection. When projecting a 16:9 & 4:3 image the image sizes, screen height