



## PLC-XT35L

- Brightness: 5,000 ANSI lumens
- Resolution, native: 1,024 x 768 (XGA), maximum: 1,600 x 1,200 (UXGA)
- Motorised horizontal and vertical lens shift function
- Professional connections (5 BNC, DVI-D)
- Symmetrical design
- 360° projection possible
- Network integration (optional) with control camera
- 5 optional lenses with bayonet lock (Standard lens: LNS-S11)
- 3 years warranty

## PLC-XT35L

TECHNICAL DATA	PLC-XT35L
Category	Business & Education
Panel	3 x 1.0" TFT p-Si (4 : 3), micro lens
Projection Lamp	330 W NSH (LMP-116)
Brightness in ANSI lumens	5,000
Lamp Life	3,000 h (eco mode)/2,500 h (normal mode)
Fan Noise	30 dB (eco mode)/33 dB (normal mode)
Standard Lens	Delivery without lens
Throw Distance Ratio	Depending on lens*
Throw Distance	Depending on lens*
Contrast Ratio	1,000 : 1
Resolution in Pixels	1,024 x 768 (XGA)
Image size min-max (diagonal)	30"-300"
Uniformity	90 %
Bandwidth/Frequency	100 + 140 MHz, horizontal 15-100 kHz, vertical 50-100 Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: DVI-D (digital/HDCP) Input 2: D-Sub15 (RGB) Input 3: 5 x BNC (RGBHV/Video/Y-Pb/Cb-Pr/Cr) Input 4: RCA (Composite) Input 5: Mini DIN 4-pin (S-Video) Audio: 3.5 mm Stereo Jack (for computer), 2 x RCA (R/L mono) for video Audio Output: 3.5 mm Stereo Jack (variable) Monitor Output: D-Sub15 Control Input Jack 1: Mini DIN 8-pin (RS232 compatible) Control Input Jack 2: USB Type B Control Input Jack 3: 3.5 mm Stereo Jack (cable remote control)
Keystone Correction	vertical +/-40°
Lens Shift	10 : 0 to 1 : 1 vertical (applies to LNS-S11/W10/T10/T11) 1 : 1 vertical (applies to LNS-W11) 1.857 : 1 to 1 : 1.857 horizontal (applies to LNS-S11/W10/T10/T11) 1 : 1 horizontal (applies to LNS-W11)
HDTV Compatibility	720p/1,035i/1,080i
Computer Compatibility	UXGA/SXGA/SXGA+/WXGA/XGA/SVGA/VGA/Mac
Zoom/Focus	Depending on lens
Power Consumption	400 W (eco mode)/455 W (normal mode)/12 W (stand-by mode)/100-240 V
Warranty	3 years, 90-days lamp warranty (max. 300 hours)
Dimensions (W x H x D)	348.1 x 156.5 x 444 mm
Weight	8.1 kg
Standard Accessories	IR cable remote control with laser pointer and mouse function, batteries, user manual (CD-ROM), USB cable, D-Sub15 cable, mouse cable (serial), PIN code label
Optional Accessories	PJ Net Organizer Plus II (POA-PN03), PJ Net Organizer Plus II with video camera (POA-PN03C), ceiling mounts: 15 cm (POA-CM01), 40-70 cm (POA-CM02), 70-110 cm (POA-CM03)
Optional Lenses	5 interchangeable lenses: Standard lens LNS-S11 (Throw Distance Ratio: 1.62-2.11 : 1) Optional wide angle lens LNS-W10 (Throw Distance Ratio: 1.24-1.61 : 1) Optional wide angle lens LNS-W11 (Throw Distance Ratio: 0.8 : 1) Optional tele lens LNS-T10 (Throw Distance Ratio: 2.12-3.46 : 1) Optional tele lens LNS-T11 (Throw Distance Ratio: 3.4-5.4 : 1)

\* You can use the distance calculator at [www.sanyo.de](http://www.sanyo.de) to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 11/2007

