



PLC-XW56

- Brightness: 2,000 ANSI lumens
- Resolution, native: 1,024 x 768 (XGA), maximum: 1,600 x 1,200 (UXGA)
- Very quiet: 25 dB in Eco mode
- Zoom: 1.2 x
- Key Lock function, Pin Code Lock for security
- MyLogo Function for custom logo transfer
- Direct Power On/Off lets you switch the projector on/off without delay
- Remote Control Code for increased user friendliness
- 3 years warranty, 1 year lamp warranty

PLC-XW56

TECHNICAL DATA	PLC-XW56
Category	Business & Education
Panel	3 x 0.6" TFT p-Si (4 : 3), micro lens
Projection Lamp	200 W UHP (LMP-107)
Brightness in ANSI lumens	2,000
Lamp Life	3,000 h (eco mode)/2,000 h (normal mode)
Fan Noise	25 dB (eco mode)/30 dB (normal mode)
Standard Lens	F = 1.65–1.83 / f = 22.5–27.0 mm*
Throw Distance Ratio	1.77–2.17 : 1*
Throw Distance	1.4–13.2 m*
Contrast Ratio	400 : 1
Resolution in Pixels	1,024 x 768 (XGA)
Image size min–max (diagonal)	40"–300"
Uniformity	85 %
Bandwidth/Frequency	140 MHz, horizontal 15–100 kHz, vertical 50–100 Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: D-Sub15 (RGB/Component/S-Video) Input 2: RCA (Composite) Audio: 3.5 mm Stereo Jack (variable), 2 x RCA (R/L mono) for video Audio Output: 3.5 mm Stereo Jack (variable) Monitor Output: D-Sub15 Control input: Mini DIN 8-pin (RS232 compatible)
Audio Function	1 W Mono
Keystone Correction	vertical +/-20°
Up/Down-Ratio	6 : 1 (Fixed U/D Ratio)
HDTV Compatibility	720p/1,035i/1,080i
Computer Compatibility	UXGA/SXGA/WXGA/XGA/SVGA/VGA
Zoom/Focus	1.2 x/manual
Power Consumption/Voltage	205 W (eco mode)/250 W (normal mode)/9 W (stand-by mode)/100–240 V
Warranty	3 years, 1 year lamp (max. 2,000 h)
Dimensions (W x H x D)	330 x 80 x 237 mm
Weight	2.9 kg
Standard Accessories	Remote control, batteries, user manual (CD-ROM), power cable, D-Sub15 cable, PIN code label
Optional Accessories	SCART/VGA cable (POA-CA-SCART), components/D-Sub15 cable (POA-CA-COMPVGA), ceiling mounts: 15 cm (POA-CM01), 40–70 cm (POA-CM02), 70–110 cm (POA-CM03)
Lenses	Standard Lens

* You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 11/2007

