

TENTATIVE

Specifications

# PDG-DXT10L

XGA TableTop Multimedia Projector



Lens sold separately

**IMPRESSIVE BRIGHTNESS AND CONTRAST RATIO**  
260W UHP 2-Lamp combined with high-contrast optical system with DynamicBlack™ technology deliver an impressive **5200** ANSI lumens of brightness and a contrast ratio of **2100:1**.

**DLP PROJECTOR WITH HIGH RESOLUTION**  
The combination of BrilliantColor™ and a six-segment color wheel (optional) offer a more true color reproduction.

**NETWORK CONTROL / ADMINISTRATION**  
Sanyo's standard RJ45 LAN feature allows for control and administration of a projector via a network. Projector status can be monitored and projector functions can be controlled through a web browser. A notification can be automatically sent via E-mail whenever the projector encounters a problem, allowing the administrator to act quickly to resolve any issues.

**HELPFUL MAINTENANCE FUNCTIONS**  
The lamp and filter maintenance functions provide for better and proper maintenance of the projector. Easy maintenance cover is provided for lamp and color wheel replacement.

**EASY POWER OFF AND ON START**  
The Easy Power Off function allows the projector to be turned off (even when projecting an image) using a power strip equipped with a switch and a breaker. The On Start function allows the projector to be turned on by supplied AC power.

**DUAL LAMP CONTROL SYSTEM**  
The two-lamp control system offers high brightness, maintained lamp life and energy savings along with redundancy. The lamp control function offers brightness of the lamp can be selected. The power management function also reduces power consumption and maintains lamp life.

**BAYONET-STYLE EASY LENS REPLACEMENT**  
Attaching the included easy lens attachment to your lenses makes installation and removal of our optional lenses quick and easy by one touch release button.



DLP® and the DLP logo are registered trademarks of Texas Instruments. BrilliantColor™ and DynamicBlack™ are trademarks of Texas Instruments.

**SANYO**  
PRESENTATION TECHNOLOGIES

21605 Plummer Street  
Chatsworth, CA 91311  
Ph: 888-337-1215 (toll-free)  
Fax 818.717.2719  
www.sanyolcd.com

Resolution	XGA (1024 x 768)
Brightness (typical)	<b>5200 ANSI Lumens</b>
Uniformity	85% (Center to corner)
DMD Panel System	0.7" XGA-LVDS DMD x 1
Number of Pixels	786,432
Contrast Ratio	2100:1 (with DynamicBlack™)
Projection Image (diagonal)	40"-500" (Dependent on Lens)
Aspect Ratio	4:3
Throw Distance	Dependent on Lens
Zoom/Focus	Dependent on Lens
Power Lens Shift	Up/Down Ratio 10:0 - 1:1 Left/Right Ratio 3:2 - 2:3 (Dependent on Lens)
Digital Keystone Correction	Vert. +/- 40°MAX, Horiz. +/- 35°MAX
Projection Lens	Lens Sold Separately
Lens Throw Ratio	Dependent on Lens
Projection Lamp	260W UHP x 2
Scanning Frequency	H 15kHz, 31-90kHz; V 50-85Hz
Dot Clock	170 MHz
Color System	PAL/PAL-M/PAL-N/SECAM/NTSC/NTSC4.43
Computer Compatibility	UXGA, SXGA+, WXGA, XGA, SVGA, VGA, MAC
Sound Output	Two-piece stereo 3W
Voltage	100-240V AC; 50/60/Hz (auto sense/select)
BTU Rating	TBD
dB Rating	TBD
Power Consumption	TBD
Dimensions (WxHxD)	19.9" x 7.8" x 15.2"
Net Weight	36.4 lbs.
User Maintenance	Clean air filters, replace lamp assembly
Input Terminal Panel 1	D-Sub 15 x 1 • Audio x1 (stereo mini jack)
Input Terminal Panel 2	RGBHV or Y/Cb/Cr (BNC x5) • Audio x1 (stereo mini jack)
Input Terminal Panel 3	DVI-D x1 (HDCP) • Audio x1 (stereo mini jack)
Input Terminal Panel 4	Component Video (RCA x3) • L & R Audio (RCA x2)
Input Terminal Panel 5	Composite Video (RCA x1) • S-Video x1 • L & R Audio (RCA x2)
Additional Input Terminals	Wired remote control jack x 1 (stereo mini jack) • USB x 1 • RS232C Control Port x 1 (D-sub 9pin) • RJ45 LAN • Remote control 15pin GPIO
Output Terminals	D-Sub 15 x 1 • Audio x1 (stereo mini-jack)
Included Accessories	Wired/Wireless I/R Remote Control • Batteries (two "AA") • AC power cord • Wired remote cable • Lens cover • Owner's manual (CD-ROM & Quick Reference Guide) • Security Sticker
Optional Accessories	• Replacement Lamp (610 335 8406) • Optional Lenses (see below) • Optional 6 segment Color Wheel RGBCMY
Warranty	Three years parts and labor; 90 days lamp; Quick Repair Program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

Optional Lens Specifications

Part No.	LNS-W41	LNS-W40	LNS-S40	LNS-T40	LNS-T41
Zoom	No	Power	Power	Power	Power
Throw Ratio	0.77:1	1.33-1.79:1	1.78-2.35:1	2.22-4.43:1	4.43-8.3:1
F Stop	2.0	1.8-2.3	1.7-1.9	2.1-2.9	2.2-3.1
Length	TBD	TBD	TBD	TBD	TBD
Weight	2.2lbs	2.4lbs	1.8lbs	2.6lbs	2.0lbs