

CASIC

TEXAS INSTRUMENTS



2500 ANSI LUMEN Portable Projector with Built-in USB



Road Warrior Designed!

The Casio Super Slim is a small but powerful projector – about the size of an 8 $\frac{1}{2}$ x 11 sheet of paper, and it fits into a briefcase together with your laptop.

2X Optical Zoom!

Use Super Slim's powerful zoom lens to properly fill your screen. Whether you're in a small office or large board room, the industry leading 2X zoom gives you the flexibility to easily position the projector.

New Color Wheel Technology!

Casio has improved the image system so that your presentations look brighter with improved color and enhanced contrast.

Projector Line-up Selection!

Casio lets you choose the model that is right for your needs. Choose from 4 models that offer brightness selection and optional wireless capability.



USB TECHNOLOGY:

- PC Free Presentations! No laptop required – Transfer your material to a USB thumb drive by using Casio's EZ-PRO Converter.
- Wireless Presentations! By using the optional YW-2L Wireless LAN adaptor, up to four laptops can be connected wirelessly to the XJ-S46.
- Casio Multi-Functional Camera System YC-430!
 Casio's multifunctional





CASIO is a registered trademark of CASIO Computer Co., Ltd. in Japan. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA is a registered trademark of International Business Machines Corporation in the United States. Windows and PowerPoint are registered trademarks of Microsoft Corporation in the USA and/or other countries. Other product names or company names on this specification sheet are either trademarks or registered trademarks of their respective owners. Specifications subject to change without notice.

Visit: www.superslimprojector.com

CASIO.

XJ-S46

SPECIFICATIONS Model : XJ-S46

Specifications		
Brightness (lumens)	Eco-Mode: OFF	2500 lumens
Brightness (lumens)	Eco-Mode: OFF	2000 lumens
Contrast Ratio	Telephoto mode	1800:1
Lamp	High-pressure mercury lamp	210W
Keystone Correction	Auto	+30°
Keystone Correction	Manual	+30° ±30°
	Manual	
Focusing	7	Manual focus (electric)
Projection Lens	Zoom ratio	Optical 2X electric zoom
Projection Screen Size Projection Range		15 ~ 300-inch
	60-inch screen	5.57 feet to 11.15 feet
	100-inch screen	9.18 feet to 18.37 feet
	Minimum	2.75 feet
	Projection ratio	1.4-2.8:1
Projection System		DLP® system
Display Element		0.55-inch DLP® chip
		786,432 pixels (1,024 x 768)
Color Reproduction		Full color (16.77 million colors)
Power Source		AC100~240V, 50/60Hz
Dimensions		10.62" x 7.83" x 1.69"
		Excluding projections (1.25" at thinnest point)
Weight		3.96 lbs.
Security Compatibility	Kensington Compatible	yes
coounty companying	Power ON password	Ves
Power Consumption	Operating	270W (Eco-Mode:220W)
Ceiling Mounting Possible		Yes:when used with the ceiling mount lamp
ace Specifications		res.when used with the ceiling mount lamp
RGB input	Input terminal	RGB mini D-Sub 15 pin x 1
Audio	input terminal	Also use as YcbCr/YPbPr input
	True resolution	XGA (1,024 x 768)
	Compressed	Maximum SXGA+ (1,400 x 1,050)
		. ,
	Input	3.5mm mini-jack
	Output	1 W speaker
		3.5mm mini-jack (sharing input terminal)
Video	Signal input	NTSC/PAL/PAL-N/PAL-M
		/PAL60/SECAM
	Input terminals	Composite: 3.5mm mini-jack
		(sharing audio terminal), YCbCr/YPbPr
USB		(sharing audio terminal), YCbCr/YPbPr Type A x 1, USB (1.1) Host
USB	Connectable	· · · · · · · · · · · · · · · · · · ·
USB	Connectable Equipment	Type A x 1, USB (1.1) Host
USB		Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2
USB		Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2 Multi-functional camera system YC-400/430
5	Equipment	Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2 Multi-functional camera system YC-400/430 USB memory (commercially available)
	Equipment Operating temperature	Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2 Multi-functional camera system YC-400/430 USB memory (commercially available) 5~35°
s Usage Environment	Equipment	Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2 Multi-functional camera system YC-400/430 USB memory (commercially available) 5~35° 20~80% (non-condensation)
s Usage Environment Lamp life (hour)	Equipment Operating temperature Operating humidity	Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2 Multi-functional camera system YC-400/430 USB memory (commercially available) 5~35° 20~80% (non-condensation) 2,000h
S Usage Environment Lamp life (hour) Remote Range *1:Front: v	Equipment Operating temperature	Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2 Multi-functional camera system YC-400/430 USB memory (commercially available) 5~35° 20~80% (non-condensation)
S Usage Environment Lamp life (hour) Remote Range *1:Front: v	Equipment Operating temperature Operating humidity within 30 degrees up, down, left, right	Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2 Multi-functional camera system YC-400/430 USB memory (commercially available) 5~35° 20~80% (non-condensation) 2,000h
S Usage Environment Lamp life (hour) Remote Range *1:Front: v	Equipment Operating temperature Operating humidity within 30 degrees up, down, left, right	Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2 Multi-functional camera system YC-400/430 USB memory (commercially available) 5~35° 20~80% (non-condensation) 2,000h 16.40 feet maximum *1
S Usage Environment Lamp life (hour) Remote Range *1:Front: v	Equipment Operating temperature Operating humidity within 30 degrees up, down, left, right	Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2 Multi-functional camera system YC-400/430 USB memory (commercially available) 5~35° 20~80% (non-condensation) 2,000h 16.40 feet maximum *1 Wireless remote controller (YT-35) AC cord
S Usage Environment Lamp life (hour) Remote Range *1:Front: v	Equipment Operating temperature Operating humidity within 30 degrees up, down, left, right	Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2 Multi-functional camera system YC-400/430 USB memory (commercially available) 5~35° 20~80% (non-condensation) 2,000h 16.40 feet maximum *1 Wireless remote controller (YT-35) AC cord RGB cable
S Usage Environment Lamp life (hour) Remote Range *1:Front: v	Equipment Operating temperature Operating humidity within 30 degrees up, down, left, right	Type A x 1, USB (1.1) Host Wireless (IEEE802.11b) Adapter YW-2 Multi-functional camera system YC-400/430 USB memory (commercially available) 5~35° 20~80% (non-condensation) 2,000h 16.40 feet maximum *1 Wireless remote controller (YT-35) AC cord