



PLC-XU115 | PLC-XU105

- Brightness: 4,500 ANSI lumens at a net weight of only 3,5 kg
- Resolution, native: 1,024 x 768 (XGA), maximum: 1,600 x 1,200 (UXGA)
- Wide angle lens with 1,6 optical zoom allows flexible positioning (1.15–1.85 : 1)
- Extensive connectivity options, including DVI-I with HDCP, as well as SD card slot for PC-less presentations (PLC-XU115)
- Network integration with LAN connector (RJ45) and integrated W-LAN (PLC-XU115)
- Network integration with Windows Vista, Windows XP, Windows 2000 and Mac (PLC-XU115)
- Key Lock function, Pin Code Lock for security
- MyLogo function, Direct Power On/Off
- 3 years warranty, 1 year lamp warranty


PLC-XU115 | PLC-XU105

TECHNICAL DATA	PLC-XU115	PLC-XU105
Category	Business & Education	
Panel	3 x 0.8" TFT p-Si (4 : 3), micro lens	
Projection Lamp	275 W NSH (LMP-111)	
Brightness in ANSI lumens	4,500	
Lamp Life	3,000 h (eco mode)/2,500 h (normal mode)	
Fan Noise	30 dB (eco mode)/34 dB (normal mode)	
Standard Lens	F = 1.7–2.5/f = 19.2–30.2 mm*	
Throw Distance Ratio	1.15–1.85 : 1*	
Throw Distance	0.93–11.47 m*	
Contrast Ratio	500 : 1	
Resolution in Pixels	1,024 x 768 (XGA)	
Image size min–max (diagonal)	40"–300"	
Uniformity	85 %	
Bandwidth/Frequency	100 + 140 MHz, horizontal 15–100 kHz, vertical 50–100 Hz	140 MHz, horizontal 15–100 kHz, vertical 50–100 Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PALM/N	
Connections	Input 1: DVI-I (digital/HDCP/analogue) Input 2: D-Sub15 (RGB/Component/SCART-RGB) Input 3: RCA (Composite) Input 4: Mini DIN 4-pin (S-Video) Input 5: RJ45 (LAN) Audio: 3.5 mm Stereo Jack for Computer, 2 x RCA (R/L mono) for video Audio Output: 3.5 mm Stereo Jack (variable) Monitor Output: D-Sub15 Audio Output: 3.5 mm Stereo Jack (variable) Control Input 1: USB type B Control Input 2: Mini DIN 8-pin (RS232 compatible) Control Input Jack 3: 3.5 mm Stereo Jack (cable remote control) Others: SD media slot, integrated wireless function	Input 1: D-Sub15 (RGB) Input 2: D-Sub15 (RGB/Component/SCART-RGB) Input 3: RCA (Composite) Input 4: Mini DIN 4-pin (S-Video) Audio: 3.5 mm Stereo Jack for Computer 2 x RCA (R/L mono) for video Audio Output: 3.5 mm Stereo Jack (variable) Monitor Output: D-Sub15 Control Input Jack: Mini DIN 8-pin (RS232 compatible)
Audio Function	1 W Mono	
Keystone Correction	vertical +/-40°	
Up/Down-Ratio	9 : 1 (Fixed U/D Ratio)	
HDTV Compatibility	480i/480p/575i/575p/720p/1,080i	
Computer Compatibility	UXGA/SXGA/SXGA+/WXGA/XGA/SVGA/VGA/Mac	
Zoom/Focus	1.6 x/manual	
Power Consumption/Voltage	269 W (eco mode)/305 W (normal mode)/12 W (stand-by mode)/100–240 V	266 W (eco mode)/302 W (normal mode)/12 W (stand-by mode)/100–240 V
Warranty	3 years, 1 year lamp (max. 1,000 h)	
Dimensions (W x H x D)	334 x 93 x 257 mm	
Weight	3.5 kg	
Standard Accessories	IR/cable remote control, batteries, user manual (CD-ROM), power cable, D-Sub15 cable, serial control cable (Mini DIN 8-D-Sub9), PIN code label, carrier bag, lens cover with fastener and cord, CD-ROM for network module	IR/cable remote control, batteries, user manual (CD-ROM), power cable, D-Sub15 cable, serial control cable (Mini DIN 8-D-Sub9), PIN code label, carrier bag, lens cover with fastener and cord
Optional Accessories	SCART/D-Sub 15 cable (POA-CA-SCART), Component/D-Sub15 cable (POA-CA-COMPVGA), ceiling mounts: 15 cm (POA-CM01), 40–70 cm (POA-CM02), 70–110 cm (POA-CM03)	SCART/D-Sub 15 cable (POA-CA-SCART), remote control with laser pointer (POA-RCKIT03), components/D-Sub15 cable (POA-CA-COMPVGA), presentation kit including mouse function (POA-RCKIT04), Ceiling mount: 15 cm (POA-CM01), 40–70 cm (POA-CM02), 70–110 cm (POA-CM03)
Lenses	Standard Lens	

* You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 04/2008



PLC-XU115 | PLC-XU105



PLC-XU105



PLC-XU115