

# PLC-XW60

XGA Ultraportable Multimedia Projector –  
It's Ultra-Light!!



### ULTRACOMPACT, FULLY PORTABLE 2000 AL XGA

Not much larger than a laptop PC, the PLC-XW60 weighs just 3.6 pounds and delivers true XGA picture quality in a flexible go-anywhere system. Also, it may be ceiling or inverse mounted to meet numerous application needs.

### SHORT THROW LENS ADVANTAGES

Equipped with a high quality short throw lens with 1.2X optical zoom, the PLC-XW60 can throw a crisp, bright 100-inch diagonal image from merely 8.9 feet away.

### AUTO SEARCH INPUT MODE / AUTO KEYSTONE

Aimed to reduce setup time the Auto Input Search performs three functions: Input Search, Auto PC Adjustment and Auto Keystone. The user no longer has to manually select input modes.

### DUAL D-SUB15 INPUTS

These inputs are just part of the advanced input selections on the PLC-XW60 SANYO projector.

### BLACKBOARD (GREEN) MODE

For more effective presentations in rooms with dark-surfaced walls, the PLC-XW60 projector features the blackboard (green) mode, which automatically adjusts white balance and gamma correction to project an intelligent image without a screen.

### SECURITY FEATURES

A four-digit PIN code lock ensures projector security. The PLC-XW60 projector cannot be operated without the correct password.

### QUICK START AND POWER-OFF AND GO

No more waiting for the projector to cool down. Simply disconnect the power cord right after the presentation without worrying about overheating.

### USER-SPECIFIED START-UP SCREEN

To create a more professional presentation, logo and image files may be captured for display during the projector's start-up countdown sequence.

### VARIABLE AUDIO OUT

This convenient feature on the PLC-XW60 allows the user to control the audio level right from the projector. This centralization of video and audio controls helps in educational applications by ensuring the technical quality of the presentation and eliminating the fuss of separate outside audio controls.



### PRESENTATION TECHNOLOGIES



21605 Plummer Street  
Chatsworth, CA 91311  
Ph: 888-337-1215 (toll-free)  
Fax 818.717.2719  
www.sanyoprojectors.com

## Specifications

Resolution	XGA (1024 x 768)
Brightness	2000 ANSI Lumens
Uniformity	85% (corner to center)
LCD Panel System	0.63" TFT Poly x 3
Number of Pixels	2,359,296 (786,432 x 3)
Contrast Ratio	400:1 for Auto Lamp
Image Size (diagonal)	40" – 300"
Aspect Ratio	4:3
Throw Distance	3.6' – 32.8'
Focus	Zoom / Focus
Zoom Ratio	1.2X
Up/Down Ratio	6:1
Digital Keystone Correction	Vertical: +/- 20%
Projection System	Dichroic mirror & X prism system w/PBS
Projection Lens	F1.77~1.99, f=0.69"~0.83"
Lens Throw Ratio	1.33-1.62:1
Projection Lamp	165W UHP
Scanning Frequency	H Sync: 15-100kHz, V Sync: 50-100Hz
Dot Clock	110MHz
Color System	PAL/PAL-M/PAL-N/SECAM/NTSC/NTSC4.43
Computer Compatibility	UXGA, WXGA, SXGA, XGA, SVGA, VGA, MAC
Sound Output	One-piece, 1-watt Mono
Voltage	100-120V/200-240V AC ; 50/60 Hz (auto sense/select)
BTU Rating	784.8 / 668.8 / 13.0 (normal/mono/stand-by)
dB Rating	34.3 bBA / 30.5 bBA (normal/eco mode)
Power Consumption	230W / 196W (normal/eco mode)
Dimensions (WxHxD)	10.4" x 2.9" x 7.4" (including protrusion)
Net Weight	3.6 lbs.
User Maintenance	Clean air filters, replace lamp assembly
PC Input Terminals	D-Sub15 x 2 (1 switchable in/monitor out) • Audio x 1 (stereo mini-jack : common)
Video Input Terminals	Composite video (RCA x 1) • S-Video(D-Sub15 input w/optional cable) • R & L/mono audio (RCA x 2) • Component video(D-Sub15 input w/optional cable) • Audio for component video(stereo mini-jack : common)
Output Terminals	D-Sub15 x 1 ( switchable in/monitor out) • Variable Audio (stereo mini-jack)
Included Accessories	I/R Remote Control • 2 AA batteries • Owner's manual (quick manual & CD-ROM) • VGA cable • PIN code Label • AC power cord • Soft carrying bag • Strap for lens cap
Optional Accessories	• 610 339 1700– Replacement lamp • 945 086 4965– Replacement remote • POA-CA-COMPVGA – VGA/Component video cable • POA-CA-VGAS – VGA/S-Video cable • POA-RCKIT04 – Presentation kit (remote control w/USB infrared receiver) • POA-MCSRL – Serial control cable
Service Port	Mini DIN 8-pin
Warranty	Three years parts and labor; 90 days original lamp; Quick repair program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



Remote Control  
945 086 4965



Rear Back Panel