



## PLC-XT21

- Brightness: 4,000 ANSI lumens
- Resolution, native: 1,024 x 768 (XGA), maximum: 1,600 x 1,200 (UXGA)
- Motorised horizontal and vertical lens shift function facilitates flexible positioning
- Professional connections (5 BNC, DVI-D)
- Network integration (optional) with control camera for maintaining and controlling the projector on the LAN
- Standard lens LNS-S10 plus 4 interchangeable lenses with bayonet lock
- 360° projection possible
- Symmetrical design
- 3 years warranty

## PLC-XT21

TECHNICAL DATA	PLC-XT21
Category	Business & Education
Panel	3 x 1.0" TFT p-Si (4 : 3)
Projection Lamp	300 W UHP (LMP-105)
Brightness in ANSI lumens	4,000
Lamp Life	3,000 h (eco mode)/2,500 h (normal mode)
Fan Noise	31 dB (eco mode)/35 dB (normal mode)
Standard Lens	F = 1.7–2.1/f = 33–43 mm
Throw Distance Ratio	1.6–2.1 : 1
Throw Distance	1.2–10.0 m
Contrast Ratio	1,000 : 1
Resolution in Pixels	1,024 x 768 (XGA)
Image size min–max (diagonal)	30"–300"
Uniformity	90 %
Bandwidth/Frequency	100–140 MHz, horizontal 15–100 kHz, vertical 50–100 Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PALM/N
Connections	Input 1: DVI-D (digital/HDCP) Input 2: D-Sub15 (RGB) Input 3: 5 x BNC (RGBHV/Video/Y-Pb/Cb-Pr/Cr) Input 4: RCA (Composite) Input 5: Mini DIN 4-pin (S-Video) Audio: 3.5 mm stereo jack for computer, 2 x RCA (R/L mono) for video Audio Output : 3.5 mm stereo jack (variable) Monitor Output: D-Sub15 Control Input Jack 1: Mini DIN 8-pin (RS232 compatible) Control Input Jack 2: USB Type B Control Input Jack 3: 3.5 mm stereo jack (cable remote control)
Audio Function	1 W Mono
Keystone Correction	vertical +/-40°
Lens Shift	10 : 0 to 1 : 1 vertical (for LNS-S10/W10/T10/T11) 1 : 1 vertical (for LNS-W11) 1.857 : 1 to 1 : 1.857 horizontal (for LNS-S10/W10/T10/T11) 1 : 1 horizontal (for LNS-W11)
HDTV Compatibility	720p/1,035i/1,080i
Computer Compatibility	UXGA/SXGA/SXGA+/WXGA/XGA/SVGA/VGA/Mac
Zoom/Focus	1.3 x/automatic focusing
Power Consumption	360 W (eco mode)/395 W (normal mode)/12 W (stand-by mode)/100–240 V
Warranty	3 years
Dimensions (W x H x D)	348.1 x 156.5 x 444 mm
Weight	8.7 kg
Standard Accessories	IR remote control with laser pointer and mouse function, batteries, user manual (CD-ROM), power cable, USB cable, D-Sub15 cable, PIN code label
Optional Accessories	PJ Net Organizer Plus II with video camera (POA-PN03C), ceiling mounts: 15 cm (POA-CM01), 40–70 cm (POA-CM02), 70–110 cm (POA-CM03)
Optional Lenses	Standard lens, 4 interchangeable lenses: Optional wide angle lens LNS-W10 (Throw Distance Ratio: 1.24–1.61 : 1) Optional wide angle lens LNS-W11 (Throw Distance Ratio: 0.8 : 1) Optional tele lens LNS-T10 (Throw Distance Ratio: 2.12–3.46 : 1) Optional tele lens LNS-T11 (Throw Distance Ratio: 3.4–5.4 : 1) PLC-XT21L (delivery without lens): 5 interchangeable lenses

\* You can use the distance calculator at [www.sanyo.de](http://www.sanyo.de) to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 04/2008

