TOSHIBA

x2000

Exceptional talents with a great appreciation of colours.

- With detachable control panel
- High security (password function and panellock)
- easy set-up and „easy to use"

3LCD

LCD stands for
Liquid Cristal Display

TOSHIBA

x2000

Immerse yourself in a world of colour.

Display 0,61" LCD Chip

Resolution XGA 1,024 x 768

Brightness 2,000 ANSI-lumens

Colour reproduction 16.7 mio. colours

Contrast 400 : 1

Projection format 4 : 3 switchable to 16 : 9

Lamp 210 W (TLPLW11LAMP)

Max. lamp life up to max. 2,000 hours/ um to max. 3.000 hours in ECO mode

Lens F = 1.6 - 1.89 / f = 18.6 - 22.3 mm, manual zoom and focus

Zoom 1.2 x

Frequency (hor./vertical) 15 - 120 kHz / 30 - 150 Hz

Projection front, rear and ceiling

Digital keystone correction auto vertikal

Input signals NTSC / PAL / SECAM, 480i, 480p, 576i, 576p, 720p, 1,080i, VGA / SVGA, XGA / SXGA / UXGA (compr.)

Inputs RGB (D-sub 15), S-video, composite video (1 x RCA), RGB audio (stereo mini jack), video / S-video audio (1 x RCA L/R)

Outputs RGB (D-sub 15), audio (stereo mini jack)

Serial interface RS-232C (mini DIN8 pin)

Power supply AC 100 - 240 V, 50 / 60 Hz

Loudspeaker 1 W mono

Dimensions (W x H x D) 295 x 81 x 255 mm

Weight 2.5 kg

Operation noise standard 34 dB / ECO mode 29 dB

Specials security-functions, user logo, password, panellock, with detachable control panel

Accessories remote control with batteries, owners manual (CD ROM), quick reference, RGB and power cable, softcase

Options ceiling mounting, trolley, spare lamp, camera c001

www.toshiba-europe.com/projectors