



## PLC-XW57

- Brightness: 2,000 ANSI lumens
- Resolution, native: 1,024 x 768 (XGA), maximum: 1,600 x 1,200 (UXGA)
- Fan noise barely audible: 26 dB in eco mode
- Flexible positioning via 1.2 optical zoom
- Key Lock function, Pin Code Lock for security
- MyLogo Function for custom logo transfer
- Direct Power On/Off lets you switch the projector on/off without delay
- Remote Control Code for increased user friendliness
- 3 years warranty, 1 year lamp warranty

## PLC-XW57

TECHNICAL DATA	PLC-XW57
Category	Business & Education
Panel	3 x 0.6" TFT p-Si (4 : 3), micro lens
Projection Lamp	200 W SHP (LMP-122)
Brightness in ANSI lumens	2,000
Lamp Life	3,000 h (eco mode)/2,000 h (normal mode)
Fan Noise	26 dB (eco mode)/31 dB (normal mode)
Standard Lens	F = 1.65–1.83 / f = 22.5–27.0 mm*
Throw Distance Ratio	1.78–2.15 : 1*
Throw Distance	1.4–13.2 m*
Contrast Ratio	600 : 1
Resolution in Pixels	1,024 x 768 (XGA)
Image size min–max (diagonal)	40"–300"
Uniformity	85 %
Bandwidth/Frequency	110 MHz, horizontal 15–100 kHz, vertical 50–100 Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL/M/N
Connections	Input 1: D-Sub15 (RGB) Input 2: D-Sub15 (RGB) or monitor output Input 3: RCA (Composite) Audio: 3.5 mm Stereo Jack for computer, 2 x RCA (R/L mono) for video Control input Jack: Mini DIN 8-pin (RS232 compatible)
Audio Function	1 W Mono
Keystone Correction	vertical +/-20°
Up/Down-Ratio	6 : 1 (Fixed U/D Ratio)
HDTV Compatibility	480i/480p/575i/575p/720p/1,035i/1,080i
Computer Compatibility	UXGA/SXGA/SXGA+/WXGA/XGA/SVGA/VGA/Mac
Zoom/Focus	1.2 x/manual
Power Consumption/Voltage	200 W (eco mode)/240 W (normal mode)/9 W (stand-by mode)/100–240 V
Warranty	3 years, 1 year lamp (max. 2,000 h)
Dimensions (W x H x D)	330 x 97.9 x 237 mm
Weight	2.9 kg
Standard Accessories	Remote control, batteries, user manual (CD-ROM), power cable, D-Sub15 cable, PIN code label, lens cover with fastener and cord
Optional Accessories	SCART/D-Sub15 cable (POA-CA-SCART), components/D-Sub15 cable (POA-CA-COMPVGA), presentation kit including mouse function (POA-RCKIT04), ceiling mounts: 15 cm (POA-CM01), 40–70 cm (POA-CM02), 70–110 cm (POA-CM03)
Lenses	Standard Lens

\* You can use the distance calculator at [www.sanyo.de](http://www.sanyo.de) to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 04/2008

