



Silverline self-locking roller / electric

The reflecta large projection screen to be fixed permanently to a wall or ceiling is mounted to an aluminum profile case and is operated either manually or motor-driven. The projection screen is extended and retracted with a space-saving and silent tube motor with integrated end position switch. With the switch, the screen can be stopped at any desired position. Optionally, the screen can be equipped with a locking mechanism to stop the screen at intermediate heights to adjust to different projection formats. Ideal for the training and communications sector.

Product details:

- Mounted to wall or ceiling.
- Electric or manual operation.
- Simple installation and easy handling.
- 8.5 cm x 8.5 cm large tube allows for space-saving installation.
- Large viewing angle.
- Suitable for all common front projection types.
- High-quality screens available in UltraLux (1.2 gain) or RearPro (1.6 gain) quality.



Solid aluminum tube



Plastic end caps for wall or ceiling installation



Warp-resistant profile



Switch of the electric Silverline

Silverline self-locking roller – Technical data (all dimensions in cm)

Ref. no.	Type	Fabric	Format	A	B	C	D	R1	R2	R3	E	F	G	J	Weight
80901	Silverline self-locking roller	UltraLux	1:1	155	160	155	160				173	8.5	8.5	162	5 kg
80911	Silverline self-locking roller	UltraLux	1:1	180	190	180	190				198	8.5	8.5	187	6 kg
80921	Silverline self-locking roller	UltraLux	1:1	200	210	200	210				218	8.5	8.5	207	7 kg
80931	Silverline self-locking roller	UltraLux	4:3	220	180	220	180				238	8.5	8.5	227	8 kg
80941	Silverline self-locking roller	UltraLux	4:3	240	180	240	180				258	8.5	8.5	247	9 kg
80904	Silverline self-locking roller	UltraLux	4:3	155	149	145	109	5	35	5	173	8.5	8.5	162	5 kg
80914	Silverline self-locking roller	UltraLux	4:3	180	168	170	128	5	35	5	198	8.5	8.5	187	6 kg
80924	Silverline self-locking roller	UltraLux	4:3	200	183	190	143	5	35	5	218	8.5	8.5	207	7 kg
80934	Silverline self-locking roller	UltraLux	4:3	220	193	210	158	5	30	5	238	8.5	8.5	227	8 kg
80944	Silverline self-locking roller	UltraLux	4:3	240	193	230	173	5	15	5	258	8.5	8.5	247	9 kg
80905	Silverline self-locking roller	UltraLux	16:9	155	132	145	82	5	45	5	173	8.5	8.5	162	5 kg
80915	Silverline self-locking roller	UltraLux	16:9	180	146	170	96	5	45	5	198	8.5	8.5	187	6 kg
80925	Silverline self-locking roller	UltraLux	16:9	200	157	190	107	5	45	5	218	8.5	8.5	207	7 kg
80935	Silverline self-locking roller	UltraLux	16:9	220	168	210	118	5	45	5	238	8.5	8.5	227	8 kg
80945	Silverline self-locking roller	UltraLux	16:9	240	179	230	129	5	45	5	258	8.5	8.5	247	9 kg
80916	Silverline self-locking roller RearPro	RearPro	180	190	180	190					198	8.5	8.5	187	6 kg
80926	Silverline self-locking roller RearPro	RearPro	200	210	200	210					218	8.5	8.5	207	7 kg
80936	Silverline self-locking roller RearPro	RearPro	220	200	220	200					238	8.5	8.5	227	8 kg
80946	Silverline self-locking roller RearPro	RearPro	240	200	240	200					258	8.5	8.5	247	9 kg

Silverline electric – Technical data (all dimensions in cm)

Ref. no.	Type	Fabric	Format	A	B	C	D	R1	R2	R3	E	F	G	J	Weight
81801	Electric professional	UltraLux		180	200	180	200				199	8.5	8.5	187	10 kg
81811	Electric professional	UltraLux		200	210	200	210				219	8.5	8.5	207	11 kg
81821	Electric professional	UltraLux		220	220	220	220				239	8.5	8.5	227	12 kg
81831	Electric professional	UltraLux		240	200	240	200				259	8.5	8.5	247	13 kg
81841	Electric professional	UltraLux		300	200	300	200				319	11	10	307	18 kg
81851	Electric professional	UltraLux		300	225	300	225				319	11	10	307	20 kg
81861	Electric professional	UltraLux		300	250	300	250				319	11	10	307	21 kg
81871	Electric professional	UltraLux		300	300	300	300				319	11	10	307	21 kg
81881	Electric professional	UltraLux		350	265	350	265				369	11	10	357	22 kg
81891	Electric professional	UltraLux		350	300	350	300				369	11	10	357	22 kg
81804	Electric professional	UltraLux	4:3	170	160	160	120	5	35	5	189	8.5	8.5	177	9 kg
81814	Electric professional	UltraLux	4:3	180	168	170	128	5	35	5	199	8.5	8.5	197	10 kg
81824	Electric professional	UltraLux	4:3	200	183	190	143	5	35	5	219	8.5	8.5	217	11 kg
81834	Electric professional	UltraLux	4:3	220	198	210	158	5	35	5	239	8.5	8.5	236	12 kg
81844	Electric professional	UltraLux	4:3	240	213	230	173	5	35	5	259	8.5	8.5	251	14 kg
81854	Electric professional	UltraLux	4:3	300	258	290	218	5	35	5	319	11	10	307	21 kg
81864	Electric professional	UltraLux	4:3	350	295	340	255	5	35	5	369	11	10	357	22 kg
81805	Electric professional	UltraLux	16:9	170	140	160	90	5	45	5	189	8.5	8.5	177	9 kg
81815	Electric professional	UltraLux	16:9	180	146	170	96	5	45	5	199	8.5	8.5	197	10 kg
81825	Electric professional	UltraLux	16:9	200	157	190	107	5	45	5	219	8.5	8.5	217	11 kg
81835	Electric professional	UltraLux	16:9	220	168	210	118	5	45	5	239	8.5	8.5	236	12 kg
81845	Electric professional	UltraLux	16:9	240	180	230	130	5	45	5	258	8.5	8.5	251	14 kg
81855	Electric professional	UltraLux	16:9	300	213	290	163	5	45	5	319	11	10	307	22 kg
81865	Electric professional	UltraLux	16:9	350	241	340	191	5	45	5	369	11	10	357	22 kg

