Compact manual





Features

Automatic stop for rolling and rerolling guarantees long lifespan of projection screen fabric.

Black border increases perceived clarity of projected image.

Crank mechanism may be easily operated when mounted on a (high) ceiling.

Easy mounting on wall, ceiling and/or in cover via integrated hanging.

Options

► Formats standard (1:1) and video (4:3).



Technical characteristics

- ▶ All projection screens are designed and manufactured according to DIN 19045 parts 1-5.
- ► Steel case. Galvanised interior and white powder-coated exterior (RAL 9016).
- ► Removable steel crank. Length is 165 cm.
- ► Matte white S: double-sided laminated vinyl on a woven glass fabric carrier with black backing; reflection value 1.0, viewing angle 50° L/R, weight approx. 425 gr/m² and thickness approx. 0.34 mm.
- ▶ Projection screen fabrics satisfy the requirements for fire-resistance of construction materials and components.
- ► Standard format (1:1) has a 2.5-cm black border on left/right side.
- ▶ Video format (4:3) has a 5-cm black border all around.

Accessories

- Ceiling brackets for mounting in high rooms or under lowered system ceilings.
 PASAC 002 length max. 100 cm
- ► To prevent image distortion during OHPprojection the following are available:
- wall brackets to place projection screen fabric under a corner PASAC 001 length 75 cm
- wall clamps to secure slat bar to the wall with slanting projection surfaces PASEL006







Screen fabric

Matte white S







Aspect ratio	Screen size hxw cm	Viewing size hxw cm	_	ninal onal inches
1:1	160x160 180x180 200x200	151x151 173x173 195x195		
	240x240	230x230		
	123x160	110x146	183	72
4:3	138x180	126x168	213	84
	153x200	143x190	254	100

mm	mm	mm	in kg	prod. code		
1711	1689	1620	10	PSMCO 001		
1911	1889	1820	12	PSMCO 002		
2131	2109	2040	14	PSMCO 003		
2531	2509	2440	18	PSMCO 007		
1711	1689	1620	9	PSMCO 004		
1911	1889	1820	11	PSMCO 005		
2131	2109	2040	13	PSMCO 006		
2531	2509	2440	17	PSMCO 008		

weight

For recommendations on the right screen fabric and size, see pages 4-7 or consult the interactive screen selector at www.projecta.nl.