Cinema electrol

IPROJECTAII



Features

Compact case with motor.

Automatic stop for rolling and rerolling guarantees long lifespan of projection screen fabric.

Supplied with extra high, black border on top to achieve ideal viewing height. see also page 4

Black border increases perceived clarity of projected image.

Easy mounting on wall, ceiling and/or in cover via integrated hanging.



- ► Screen fabrics Matte white S and High Contrast S
- ► Formats video (4:3) and HDTV (16:9).

Accessories

- ► Ceiling brackets for mounting on recessed ceilings or ceilings starting at 2.8 metres high. PASAC 002 length max. 100 cm
- ▶ Infrared remote control has a range of 7 metres and comprises a wall box with infrared receiver and transmitter. PASEL 012
- ► Cordless radio frequency remote control for distances up to 30 metres. Three-part set comprising a control module, cordless switch and a transmitter. PASEL 013





▲ Electrically operated projection screen equipped with an extra high black border on top for optimum viewing height, very suitable for Home Cinema and/or high rooms.


Technical characteristics


- ▶ All projection screens are designed and manufactured according to DIN 19045 parts 1-5.
- ► Steel case. Galvanised inner side and white powder-coated outside (RAL 9016).
- ▶ Matte white S: double-sided laminated vinyl on a woven glass fabric carrier with black backing; reflection value 1.0, viewing angle 50° L/R, weight approx. 425 gr/m² and thickness approx. 0.34 mm.
- ▶ High Contrast S: double-sided coated grey vinyl on a woven glass fabric carrier with black backing; reflection value 1.0, viewing angle 45° L/R, weight approx. 540 gr/m² and thickness approx. 0.36 mm.
- ► Screen fabric(s) satisfy the requirements for fire-resistance of construction materials and components.
- ▶ In addition to a 5-cm. black border all around, Video (4:3) and HDTV (16:9) formats also have an extra high, black border.
- ► All of the electrical motors comply with: EN 60335; IEC 61000; 89/336/EWG; 89/392/EEG and supplements: 91/638/EEG and 93/44/EEG.
- ▶ Motor with 5-year guarantee and CE quality mark.
- ► Somfy motor with 17 RPM (revolutions per minute) and 90 Watts.
- ► Supplied complete with 3-metre connection cable and separate wall switch (CE quality mark).











Aspect Screen ratio size hxw cm		Viewing size hxw cm	diag	Nominal diagonal cm inches		Case L2 mm	L3 mm	Net weight in kg	Up/down in sec.		en fabrics 5 High Contrast S prod. code	Max. screen fabric length in cm	
	123x160	110x146	183	72	1711	1689	1620	11	31	PSECI 004	PSECI 012	182	62
4:3	138x180	126x168	213	84	1911	1889	1820	13	31	PSECI 005	PSECI 013	182	46
	153x200	143x190	254	100	2131	2109	2040	15	31	PSECI 006	PSECI 014	182	29
	90x160	82x146	165	65	1711	1689	1620	11	31	PSECI 007	PSECI 015	182	90
16:9	102x180	95x168	208	82	1911	1889	1820	13	31	PSECI 008	PSECI 016	182	77
10.9	117x200	107x190	234	92	2131	2109	2040	15	31	PSECI 009	PSECI 017	182	65

For recommendations on the right screen fabric and size, see pages 4-7 or consult the interactive screen selector at www.projecta.nl.